

3" Label Printer



LP-3150TN

- 3 inch print width
- 6 inch/sec ultra high print speed
- Support 2D barcode printing
- Thermal continuous and sticker paper supported
- Label paper auto positioned
- Module design for different application
- Support print media in 16mm to 82mm range, easy operation design
- Paper auto checkout and temperature auto controlled function
- Simplified Chinese, Traditional Chinese and Korean character supported
- Label paper peel-off and tear-off modes optional
- Compatible with various label software
- BMP, PCX, BAS files download and storage supported

Model		LP-3150TN
Print	Print method	Direct thermal line
	Print width	3inch
	Resolution	203dpi
	Print speed	3~6inch/s
	Interface	Serial+USB+Ethernet, Parallel+USB
	Media	Diameter:25~85mm; Width:16~82mm
	Print head	Temperature sensor: thermal sensitive resistance; Position sensor: microswitch
	Paper presence	Photoelectricity sensor
Character & Barcode	Enlargement	1to10 times enlargement in both directions. 0°, 90°, 270°, 360°rotation
	Barcode type	CODE128/EAN128/ITF/CODE39/CODE93/EAN13/EAN13+2/EAN13+5/EAN8/EAN8+2 EAN8+5/CODABAR/POSTNET/JPC-A/UPCA+2/UPCA+5/UJC-E/UPCE+2/UJC-E+5 CPOST/MSI/MSIC/PLESSEY/ITF14/EAN14/QRCODE(GP-3150TI)
	Character Size	FONT 0 to FONT 8 Simplified/Traditional Chinese /Korean
	Fonts	GB2312
Buffer	Data	2M bytes
	NV Flash	2M bytes
Power	Cashdrawer out	DC 24V/1A
	Power supply	DC 24V/2A
	Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 24V/2A
Physical Properties	Weight	1.65kg
	Dimension	230 x 158 x 147mm(L x W x H)
Environment	Work environment	Temperature: 0 ~ 45°C, Humidity: 10 ~ 80%
	Storage environment	Temperature: -10 ~ 60°C, Humidity: 10 ~ 90%
Reliability	Mechanism	150km

Contact Us

Singapore Office (Main)

2 Sims Close, Gemini@Sims Singapore 387298

T (+65) 6742 9255

E sales@paclin.com.sg